

# RS3系列半导体器件保护用快速熔断体



## 适用范围

---

RS3系列熔断器额定电压交流(50Hz/60Hz)至750V额定电流至1000A用于半导体器件及其成套装置的短路保护。

符合标准 GB 13539.4 IEC 60269

型号	额定电压(V)	额定电流(A)	尺寸				
			a	b	c	d	Φ
RS3-50	250	15,20,25,30,40,50	115±2.0	100±1.0	25±0.5	45±0.5	7
RS3-50	500	15,20,25,30,40,50	135±2.0	120±1.5	25±0.5	45±0.5	7.5
RS3-100	250	50,60,80,100	120±1.5	100±1.0	40±1.0	42.5±1.0	7×10.5
RS3-100	500	50,60,80,100	140±2.0	120±1.5	40±1.0	42.5±1.0	7×10.5
RS3-200	250	120,125,150,180,200	125±1.5	100±1.0	46±1.0	50±1.0	9×13.5
RS3-200	500	120,125,150,180,200	145±2.0	120±1.5	46±1.0	50±1.0	9×13.5
RS3-400	250	200,250,300,320,350,400	130±1.5	100±1.0	55±1.0	61±1.0	9×13.5
RS3-400	500	200,250,300,320,350,400	150±1.5	120±1.5	55±1.0	61±1.0	9×13.5
RS3-500	500	250,300	135±1.5	120±1.5	66±1.0	72±1.0	11×17
RS3-600	250	450,480,500,600	135±1.5	100±1.0	66±1.0	72.5±1.0	13×19.5
RS3-600	500	450,480,500,600	157±2.0	120±1.5	66±1.0	72.5±1.0	13×19.5
RS3-1000	500	700,750,800,1000,1200	173±2.5	135±1.0	86±1.0	93±1.0	17

## 订货须知

订货时必须指明：熔断体应指产品型号、额定电流、数量；

- 订货示例：RS3-400/300A 100只，表示订型号RS3-400 额定电流为300A的熔断体100只。